

## Carbon Dioxide



The Premium Range Carbon Dioxide (CO<sub>2</sub>) fire extinguisher is available in 2kg and 5kg models. Both models come complete with the distinctive Jactone colour coded handle and header label and are LPCB and Kitemark certified to BS EN3, UKCA and CE marked. Suitable for use on Class B and electrical fires. CO<sub>2</sub> leaves no residue after use and will not harm machinery or electrical equipment.

- › Quality aluminium cylinders.
- › High quality valves and discharge horn assemblies.
- › Colour coded headers and handles.



MADE IN THE UK



COLOUR CODED



FULLY CERTIFIED



5 YEAR GUARANTEE



› EC2F : 2kg CO2 with Frost Free Horn

› EC5 : 5kg CO2

## Product Certification and Specification



Cert/LPCB ref. 783b/03  
Cert/LPCB ref 783b/04



KM 57904  
BS EN 3



0086



2797



- › EXTINGUISHER :
- › PRODUCT CODE :
- › MEDIUM :
- › FIRE RATING :
- › OPERATING TEMPERATURE :
- › AVERAGE DISCHARGE TIME :
- › HEIGHT & DIAMETER :
- › FILLED WEIGHT & EMPTY WEIGHT :
- › PACKING SPEC (HxWxD) :

2kg CO <sub>2</sub> with Frost Free Horn
EC2F
Carbon Dioxide
55B
-20 °C to +60 °C
9.7 seconds
Height 500mm   Diameter 117mm
Filled 5.02kg   Empty 3.02kg
524 x 185 x 130mm

5kg CO <sub>2</sub>
EC5
Carbon Dioxide
70B
-20 °C to +60 °C
16.8 seconds
Height 670mm   Diameter 152mm
Filled 11.8kg   Empty 6.8kg
690 x 226 x 160mm