PREMIUM

Powder A B F 4

The Premium Range Powder fire extinguisher is made in our UK factory and is available in 2kg, 4kg, 6kg and 9kg ABC powder models. For use on Class A, B and C fires making them suitable for use in environments containing multiple fire risks. They are highly effective against petrol and volatile liquids which makes them ideal for vehicle protection. All models come complete with the distinctive Jactone colour coded handle, header label and base* and are Kitemark certified to BS EN3, UKCA and CE marked.

- > Quality deep drawn cylinders*.
- > High quality heavy-duty brass valves.
- > Colour coded headers, handles and bases*.









MADE IN THE UK COLOUR CODED FULLY CERTIFIED

*4kg, 6kg and 9kg models only.







EPS9:9kg ABC Powder

Product Certification and Specification









- > EXTINGUISHER :
- > PROPELLANT:
- > FIRE RATING :
-) OPERATING TEMPERATURE :
- **OPERATING PRESSURE:**
- HEIGHT & DIAMETER:
- > FILLED & EMPTY WEIGHTS:
- > PACKING SPEC (HxWxD):

- > PRODUCT CODE:
-) MEDIUM:

- AVERAGE DISCHARGE TIME :

2kg ABC Powder EPS2

ABC 40 Dry Powder

Nitrogen gas

13A | 70B | C

-20°C to +60°C 15 bar at 20°C

9.5 seconds

H 391mm | D 108mm

F 3.2kg | E 1.2kg 393 x 159 x 117mm EPS4

ABC 40 Dry Powder Nitrogen gas

21A | 113B | C -20°C to +60°C

15 bar at 20°C

12.9 seconds H 411mm | D 160mm

F 6.95kg | E 2.9kg 415 x 175 x 175mm EPS6 ABC 40 Dry Powder

Nitrogen gas 27A | 183B | C

-20°C to +60°C 15 bar at 20°C

16.1 seconds

H 517mm | D 160mm F 9.55kg | E 3.5kg

529 x 177 x 177mm

EPS9 ABC 40 Dry Powder Nitrogen gas 43A | 233B | C -20°C to +60°C 15 bar at 20°C

16.7 seconds H 552mm | D 189mm F 13.6kg | E 4.5kg

549 x 205 x 205mm

Issue 24.0