

Wet Chemical

The Premium Range Wet Chemical fire extinguisher is made in our UK factory and is available in 3 litre and 6 litre models. All models come complete with the distinctive Jactone colour coded handle, header label and base and are LPCB certified to BS EN3, UKCA and CE marked. Specifically designed for use on Class F fires (cooking oil and fats). They are also suitable for use on Class A fires.

- › Quality deep drawn cylinders.
- › High quality heavy-duty brass valves.
- › Thermoplastic lining.
- › Colour coded headers, handles and bases.
- › Spray nozzle complies with the dielectric test of BS EN3-7, clause 9.



› EWCS3H : 3 Litre Wet Chemical with Hose

› EWCS3 : 3 Litre Wet Chemical with Lance

› EWCS6H : 6 Litre Wet Chemical with Hose

› EWCS6 : 6 Litre Wet Chemical with Lance

SUITABLE FOR FAT FRYERS UP TO 25 LITRES OIL CAPACITY

SUITABLE FOR FAT FRYERS UP TO 75 LITRES OIL CAPACITY

Product Certification and Specification



Cert/LPCB ref. 783a/01
Cert/LPCB ref 783a/02



- › EXTINGUISHER :
- › PRODUCT CODE :
- › MEDIUM :
- › PROPELLANT :
- › FIRE RATING :
- › OPERATING TEMPERATURE :
- › OPERATING PRESSURE :
- › AVERAGE DISCHARGE TIME :
- › HEIGHT & DIAMETER :
- › FILLED & EMPTY WEIGHTS :
- › PACKING SPEC (HxWxD) :

3 Litre Wet Chemical	3 Litre Wet Chemical	6 Litre Wet Chemical	6 Litre Wet Chemical
EWCS3H (Hose Model)	EWCS3 (Lance Model)	EWCS6H (Hose Model)	EWCS6 (Lance Model)
Wet Chemical	Wet Chemical	Wet Chemical	Wet Chemical
Nitrogen gas	Nitrogen gas	Nitrogen gas	Nitrogen gas
25F 8A	25F 8A	75F 13A	75F 13A
+5°C to +60°C	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C
8 bar at 20°C	8 bar at 20°C	8 bar at 20°C	8 bar at 20°C
28.4 seconds	28.4 seconds	51.3 seconds	51.3 seconds
H 353mm D 160mm	H 353mm D 160mm	H 517mm D 160mm	H 517mm D 160mm
F 6.68kg E 3.10kg	F 6.68kg E 3.10kg	F 11.08kg E 4.16kg	F 11.08kg E 4.16kg
529 x 177 x 177mm	529 x 177 x 177mm	529 x 177 x 177mm	529 x 177 x 177mm