

Powder

The Marine Range Powder fire extinguisher is available in 2kg, 4kg, 6kg and 9kg ABC powder models, approved to Merchant Shipping (Marine Equipment) Regulations SI 2016/1025. For use on Class A, B and C fires making them suitable for use in environments containing multiple fire risks. They are highly effective against petrol and volatile liquids which makes them ideal for vehicle protection. All models come complete with the distinctive Jactone colour coded handle, header label and base* and are Kitemark certified to BS EN3, UKCA and CE marked.

- Quality deep drawn cylinders*.
- High quality heavy-duty brass valves.
- Colour coded headers, handles and bases*.



MADE IN THE UK



COLOUR CODED



FULLY CERTIFIED



5 YEAR GUARANTEE

*4kg, 6kg and 9kg models only.



➤ EPS2MED : 2kg ABC Powder

➤ EPS4MED : 4kg ABC Powder

➤ EPS6MED : 6kg ABC Powder

➤ EPS9MED : 9kg ABC Powder

Product Certification and Specification



0832



bsi.
Portable Fire
Extinguishers
KITEMARK™

KM 57904
BS EN 3



0086



2797



- EXTINGUISHER :
- PRODUCT CODE :
- MEDIUM :
- PROPELLANT :
- FIRE RATING :
- OPERATING TEMPERATURE :
- OPERATING PRESSURE :
- AVERAGE DISCHARGE TIME :
- HEIGHT & DIAMETER :
- FILLED & EMPTY WEIGHTS :
- PACKING SPEC (HxWxD) :

2kg ABC Powder	4kg ABC Powder	6kg ABC Powder	9kg ABC Powder
EPS2MED	EPS4MED	EPS6MED	EPS9MED
ABC 40 Dry Powder	ABC 40 Dry Powder	ABC 40 Dry Powder	ABC 40 Dry Powder
Nitrogen gas	Nitrogen gas	Nitrogen gas	Nitrogen gas
13A 70B C	21A 113B C	27A 183B C	43A 233B C
-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
15 bar at 20°C	15 bar at 20°C	15 bar at 20°C	15 bar at 20°C
9.5 seconds	12.9 seconds	16.1 seconds	16.7 seconds
H 391mm D 108mm	H 411mm D 160mm	H 517mm D 160mm	H 552mm D 189mm
F 3.2kg E 1.2kg	F 6.95kg E 2.9kg	F 9.55kg E 3.5kg	F 13.6kg E 4.5kg
393 x 159 x 117mm	415 x 175 x 175mm	529 x 177 x 177mm	549 x 205 x 205mm